MANUFACTURER AND TURN-KEY SUPPLIER
OF GEOTHERMAL SYSTEM COMPONENTS

Technical data sheet – *PE-chamber EASY*

UPDATE STATUS: 11/2018

Circles	2-8	
Standard design	accessible max. 1500kg	
Tested load	passenger car	
Material	PE	
Height excl. chamber extension	580mm	860mm
Chamber foot point	680x680mm	
Outer diameter lid	770mm	
Connection Probes	from Ø 32mm	
Connection heat pump	from Ø 32mm	
Spout- distance	100mm [Spout welded with a chamber wall]	
Delivery	Delivery on one-way palett	

Standard equipment

Outward: ball valves PVC to lock-up one single circuit
Return flow: ball valves PVC or flowmeter made of plastic

Backfilling and deaeration (constructed as a ball valve PVC 1” male)

Connection probes: O.D. 32mm or O.D. 40mm (6-8 ports both-sided)
Connection heat pump: Ø 63mm; 6-8 ports Ø 75mm
Manifold: Ø 63mm; 6-8 ports Ø 75mm

Against surcharges:
Shut-off ball valve,
Telescope chamber extension 40cm
Flowmeter made of brass

MANIFOLDS ARE PRESSURE-TESTED

WARNING ! THE DISTRIBUTOR CONNECTIONS HAVE TO BE INSTALLED ZERO-POTENTIAL.
READ, KEEP, HEED, AND FOLLOW ALL INSTRUCTIONS OBTAINED IN THE MANUAL/USERS GUIDE.

Terra Calidus GmbH – Siemensstraße 37 D-07546 Gera
tel.: 0049365 5161 8989 Fax: 0049365 5161 8988 e-mail: info@terra-calidus.de